

NT SEALANT Product number # NTS-32 / 8

PRODUCT

NT SEALANT Is a clear water-base complete Car Bodywork treatment and fiberglass surfaces (Boats) generating an anti-stick and easy-to-clean surfaces.

The applied material produces a three-dimensional net matrix that reduces the sticking ability of dust and dirt on metal surfaces.

Water pearls easily off. Enhance original colors providing **high gloss effect**.

CONDITION OF SUBSTRATE

The substrate to be coated must be clean from dust, oil, and water, grease-free, absolutely dry. The substrate temperature must be between 41° F. 86° F, the relative humidity at 30 - 80 %.

Before using, make a test on a small area to make sure the material will not be affected.

PRODUCT APPLICATION TOOLS

After bodywork or fiberglass surfaces cleaned, **NT SEALANT** must be applied by rubbing on with microfiber applicator pad or by spraying and afterward rubbing in.

The material has to be rubbed on the surface in a thin film. **Wear nitrile gloves and a mask while using the product.**

Keep away from open fire and make sure for good ventilation.

APPLICATION

Pre-Cleaning and Complete removing of minor scratches is highly recommended

- 1- Polish the paint to remove minor scratches.
- 2- Wash the surface with High-pressure machine (wide sprinkler) with clear water
- 3- Apply foam cleaner or snow foam.

Preparation: Apply a generous amount of **NT RESTORE** to an Eliminator Pad or to a common medium / hard pad. Rub the pad firmly in a small circular pattern over the surface until it is fully restored. Do a small area at a time. Allow drying until appears chalky. Buff using a microfiber cloth. Apply a second coat if necessary.

The use of a medium-hard pad buffing machine is recommended for application on large surfaces or to facilitate polishing on a medium surface. You can also use the buffing machine to remove it, once dry using a circular microfiber.

Important: After using the **NT RESTORE**, once it has been dried and removed, clean the surface with 75% water 25% alcohol compound to remove the chemical residues of previous detergents and the NT Restore residues.

Avoid direct sunlight ! Apply the coating in dry conditions and never in rain.

Application: After cleaning **NT SEALANT** is applicate by rubbing on or by spraying and afterwards rubbing in. The material has to be rubbed on the surface in a thin film.

Drying : The coated surface has to be dried for 30 – 60 min. at room temperature.

Finishing: Just wipe off remaining residues. No tools required, use a soft and clean microfiber cloth.

Maintenance: **NT NANO BLUE** reduces the surface tension and allow surfaces to stay clean for five times longer, using fewer products and **cleaning less often**. It replaces a multitude of products, glass cleaners, polishers, and others.

The effect will last up **6 months**.

Microfiber cloth must be wash with hot water, no bleach no softener. Do not iron.

Our products are specifically designed to substantially reduce the time and effectiveness of cleaning and maintenance processes, with the consequent economic savings for companies and individuals in products and working time.

SAFETY INSTRUCTIONS

In case of inhalation: Move injured person into the fresh air, keep warm and allow to rest.

In case of skin contact: Change contaminated clothing after contact with skin, wash immediately with soap and plenty of water.

In case of eye contact: Rinse immediately with plenty of water for at least 10-15 minutes.

In case of ingestion: Rinse mouth immediately.

After swallowing: Instantly call the doctor / poison center. Do not induce vomiting.

General information: Consult a physician if problems persist. In case of indisposition seek medical advice.

Keep out of reach of children.

MSDS available at info@nanotrixx.com

Our Application Department is available to answer technical questions on performance, use and chemical specifications. We provide information and advice on application technologies and relevant regulations based upon our current knowledge and opinion. WE MAKE NO REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, WITH RESPECT TO SUCH INFORMATION OR ITS APPLICATION. Customers must independently determine the suitability of our products for the customer's intended product, use or process. Customer is responsible for observing all laws and regulations relevant to such products, uses or processes.

CONTACT US

+1 954-534-4718 info@nanotrixx.com Fort Lauderdale (FL) USA **VERSION 3.0 DATE 09/ 18**