

NT STONE Product number # NTST-32

PRODUCT

NT STONE is clear Coating particularly suitable for smooth absorbent and porous mineral surfaces. It provides long-lasting protection against water, moisture and dirt entrance on mineral surfaces. Bonds exceptionally well on rough stone and concrete surfaces. It is ready-to-use and protects against weathering, UV, graffiti, paint, oil splash, fouling, and moisture, etc. Preserves and maintains the original appearance of the treated surfaces for a long period of time.

Non-yellowing properties.

CONDITION OF SUBSTRATE

The substrate to be coated must be cleaned, grease-free and **absolutely dry**.

On areas that are difficult to reach, such as cavities or drainage channels, etc. they must be dried additionally with absorbent cloths or blown dry with compressed air. On contact with a damp substrate surface, **NT STONE** reacts prematurely and cannot form a permanent seal.

Before using, make a test on a small area to make sure the material will not be affected.

PRODUCT APPLICATION TOOLS

NT STONE is supplied ready to use. Depending on the substrate it can be applied with brush, microfiber pad applicators or paint rollers (microfiber-flocking). The product is also suitable for spray application. **Use mask and nitrile gloves.**

APPLICATION

STEP 1 The substrate to be coated must be cleaned, grease-free and previous cleaners residues must be removed with clean water. The substrate must be **absolutely dry for application** . On areas that are difficult to reach, such as cavities or drainage channels, etc. they must be dried additionally with absorbent cloths or blown dry with compressed air.

STEP 2 Removes and repairs scratches and no fixed cemented portions. Mask non-mineral areas such as metal, plastic, textile.

STEP 3 Apply the solution with a spray gun, brush or roller. All areas must be covered. (Use brush recommended) Leave the product on the applied surface for one hour and remove the excess, if necessary use an small product quantity.

STEP 4 Re-apply one-second layer within minutes of the first layer depending on the level protection required.

The effect of the product will last at least **48 months**.

The used microfiber cloth have to be washed with hot water, no bleach or fabric softener. Do not iron

Our products are specifically designed to substantially reduce the time and effectiveness of cleaning and maintenance processes, with the consequent economic savings for companies and individuals in products and working time.

SAFETY INSTRUCTIONS

In case of inhalation: Move injured person into the fresh air, keep warm and allow to rest.

In case of skin contact: Change contaminated clothing after contact with skin, wash immediately with soap and plenty of water.

In case of eye contact: Rinse immediately with plenty of water for at least 10-15 minutes.

In case of ingestion: Rinse mouth immediately.

After swallowing: Instantly call the doctor / poison center. Do not induce vomiting.

General information: Consult a physician if problems persist. In case of indisposition seek medical advice.

Keep out of reach of children.

MSDS available at info@nanotrixx.com

Our Application Department is available to answer technical questions on performance, use and chemical specifications. We provide information and advice on application technologies and relevant regulations based upon our current knowledge and opinion. **WE MAKE NO REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, WITH RESPECT TO SUCH INFORMATION OR ITS APPLICATION.** Customers must independently determine the suitability of our products for the customer's intended product, use or process. Customer is responsible for observing all laws and regulations relevant to such products, uses or processes.

CONTACT US

+1 954-534-4718 info@nanotrixx.com Fort Lauderdale (FL) USA **VERSION 3.0 DATE 09/ 18**